

WWW.GABRAUN.COM



# Top/Side Loading

WASHER/EXTRACTOR

## Braun TSL Washer/Extractor



### Braun TSL Washer/Extractor

Put gravity on your side, with the **Braun Top/Side Loader**. During loading, the Braun TSL exposes the large cylinder door opening directly to the line of gravity. At the end of the cycle, Braun provides an obstruction-free, fast gravity-assisted unload.

Because it's a Braun, the TSL gives you ease of maintenance and extraordinary durability. Versatility is yours, too, with split two-pocket and three-pocket models, and capacities of 200, 400, 600 and 800 pounds.

The Braun Neutron Suspension System isolates vibration and allows placement of your TSL on any floor capable of supporting the static load of the machine.

And every TSL comes standard with the Braun Microprocessor to promote efficiency, make the most of manpower, and to save money for your operation.

Program individual TSL's directly at the front panel or exchange programs between different TSL's from a remote office computer or portable laptop with Braun Windows-based WASHNET® software.

*Works with gravity to speed loading and unloading to maximize productivity.*



**TSL Model 800**

Proper machine design and gravity make fast, effortless loading and unloading possible. The Braun TSL incorporates this feature best. And the cylinder door positions down to just 37" for easy hand loading, too.



**TSL Model 400 Medicare**

Braun Medicare TSL Washer-Extractors are designed for laundries requiring a contamination-free, clean room environment. Soiled laundry loads from one side; clean laundry unloads from the other. A full wall barrier and patented Mediflow negative air-flow system prevent cross-contamination.



**TSL Model 400**

Top/Side Loader loading & unloading convenience is available in a full range of sizes, from the 200 pound model all the way up to 800 pound capacity.



The **Braun Microprocessor** allows you to pre-program and time every cycle, plus water temperature and level, to the nth degree. Automatic cylinder positioning further enhances the smooth loading and unloading of the TSL. Digital readouts keep you posted at all stages. Safe and secure, the Braun Microprocessor is sealed against both the laundry room environment and unauthorized tampering with programs and formulas.

# Top/Side Loading Washer/Extractor

## Standard Features

- Fast gravity loading & unloading
- Braun Neutron Suspension to isolate vibration from workplace
- Rugged design and construction
- Microprocessor controls

## Specifications

TSL Model	Max. Recommended Capacity – lbs./Kg	Cylinder Dia. x Depth – Inches/mm	Cylinder Volume – Cubic Ft./Cubic Meters	Cylinder Door Area Open for Loading – Sq. Inches/Sq. cm	Extract Motor – H.P.*	Extract Speed – R.P.M.*	Wash Motor – H.P.	Wash Speed R.P.M.**	Hgt. of Unloading Doors Above Floor – Inches/mm	Automatic Drain Valves – Inches/mm	Automatic Inlet Valves – Inches/mm	Steam Valve – Inches/mm	Overall Width – Inches/mm	Overall Depth – Inches/mm	Overall Height – Inches/mm	Approx. Domestic Shipping Wt. (Net) – Lbs./Kg	Approx. Export Shipping Wt. – Lbs./Kg	Export Cubage Cubic Ft./Cubic Meters
200 Neutron	230 105	46x45 1168x1143	43.3 1.125	600 3871	10	612	3	35	37 940	6 152	2 51	3/4 19	84 2135	75 1905	91 2310	9300 4218	10,800 4898	431 12.3
200 Neutron Medicare	230 105	46x45 1168x1143	43.3 1.125	600 3871	10	612	3	35	37 940	6 152	2 51	3/4 19	84 2135	68 1730	91 2310	9900 4490	11,300 5125	431 12.3
400 Neutron	450 204	60x45 1524x1143	73.6 2.085	600 3871	20	554	7.5	26.5	37 940	8 203	2 51	1 1/4 32	95 2415	93 2360	105 2670	12,700 5760	14,600 6621	644 18.25
400 Neutron Medicare	450 204	60x45 1524x1143	73.6 2.085	600 3871	20	554	7.5	26.5	37 940	8 203	2 51	1 1/4 32	95 2415	88 2235	105 2670	13,800 6259	15,200 6893	644 18.25
600 Neutron	700 317	60x66 1524x1676	107.9 3.057	600 3871	25	554	10	26.5	37 940	8 203	3 76	1 1/4 32	111 2820	95 2415	107 2720	15,800 7165	18,300 8299	786 22.26
600 Neutron Medicare	700 317	60x66 1524x1676	107.9 3.057	600 3871	25	554	10	26.5	37 940	8 203	3 76	1 1/4 32	111 2820	88 2235	107 2720	16,400 7438	18,900 8571	786 22.26
800 Neutron	900 408	60x91 1524x2311	148.8 4.215	1200 7742	30	554	15	26.5	37 940	(2)8 (2)203	3 76	1 1/4 32	141 3580	95 2415	107 2720	21,350 9683	23,120 10485	937 26.54
800 Neutron Medicare	900 408	60x91 1524x2311	148.8 4.215	1200 7742	30	554	15	26.5	37 940	(2)8 (2)203	3 76	1 1/4 32	141 3580	88 2235	107 2720	22,850 10,363	23,870 10825	937 26.54

Standard Electrical Specifications: 208, 240 or 480 volts, 3 phase, 60 Cycle A.C.

For any characteristics other than the above consult G. A. Braun Inc., Syracuse, N.Y.

\*Two-speed extract available in all models. Low speed extract will function at one half the listed R.P.M. and H.P.

\*\*Variable Speed Drive (VSD) is available on all models.

Specifications subject to change without notice.

For more information on these and other products for the modern laundry, contact the authorized Braun dealer in your area or call G. A. Braun, Inc.



ISO 9001:2000 CERTIFIED

### G. A. Braun, Inc.

461 East Brighton Avenue  
P.O. Box 70  
Syracuse, NY 13205-0070

1-800-ID BRAUN  
(1-800-432-7286)  
(315) 475-3123  
Fax (315) 475-4130

Parts Help Desk  
1-800-432-7286 X 3

Service Help Desk  
1-800-432-7286 X 2

Textile Finishing Division  
Fort Lauderdale, FL

1-800-ID BRAUN  
(1-800-432-7286)  
Parts Fax (954) 971-3126

